

EMPLOYEE TRAINING RECORD		
TRAINING TITLE AIRLESS PAINT SPRAYER		
KEY TEACHING POINTS		
PERSONAL PROTECTIVE EQUIPMENT		
<ul style="list-style-type: none">• Safety shoes/boots• Eye and face protection, as needed.		
<ul style="list-style-type: none">• Respiratory protection, as needed		
SAFE OPERATING PROCEDURES		
<ul style="list-style-type: none">• Review safe practice rules for applicable equipment (including rental equipment) and perform pre-operational checks.• Read and follow the operator’s manual for the particular sprayer you are using.• Keep fingers and hands away from spray nozzle. Never direct the spray gun towards any part of your body. Paint could enter your skin, causing serious injury.• Do not change nozzle tip without shutting pump off and releasing the pressure. Lock spray gun trigger open.• Do not leave sprayer unattended unless it is shut off and the pressure released.• Check hoses to ensure that there are no kinks, bends or abrasions. Periodically check hose condition to ensure that ruptures do not occur.• When making repairs or replacements, use only high pressure fittings designed for use with high pressure sprayers.• Do not operate the gun without a tip guard.• When cleaning the unit, spray at minimum pressure with nozzle tip removed. Static electricity buildup may result in an explosion if flammable vapors are present.• Ensure that all machine guards are in place, if equipped.• Do not spray any paint without proper ventilation or respiratory protection.• No smoking or open flame within 50 feet of sprayer when using solvent-based paints.• Have at least a 5 pound BC fire extinguisher nearby when using solvent based paints.• Do not check for leaks with your hands. Use a piece of cardboard ro wood to detect small leaks; fluid under pressure can enter your skin, causing serious injury.		
TEST		
QUESTION	ANSWERS	
	TRUE	FALSE
1 Do not operate the gun without a tip guard.		
2 Do not spray any paint without proper ventilation or respiratory protection.		
3 Have at least a 5 pound BC fire extinguisher nearby when using solvent based paints.		
4 Do not leave sprayer unattended unless it is shut off and the pressure released.		
5 Do not change nozzle tip without shutting pump off and releasing the pressure. Lock spray gun trigger open.		
EMPLOYEE’S NAME	EMPLOYEE’S SIGNATURE	DATE
SUPERVISOR’S NAME	SUPERVISOR’S SIGNATURE	DATE
1 T 2 T 3 T 4 T 5 T		